

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

DATASHEET

FUJITSU ESPRIMO E3521 E-STAR 5.0 DESKTOP PC

YOUR FLEXIBLE ECONOMY PC

ESPRIMO E3521 E-STAR 5.0

The ESPRIMO E3521 E-Star5 is the right choice for major customers requiring the latest standard technology. This Small Form Factor PC, less than 13 litres in volume, combines top performance and extremely attractive prices. Equipped with a power supply unit with up to 87% efficiency and selected components it complies with the ENERGY STAR® standard, thus saving energy and protecting the environment. Freely configurable, with proven technology and an extended product lifecycle of 12 months, this PC is the perfect choice for cost-driven projects.



EXCELLENT PRICE / PERFORMANCE RATIO

Cost-effective system for major customer projects

- Entry-level PC with standard technology

FLEXIBILITY

Freedom of choice with tailored systems, perfect fit for specific requirements

- Flexible logistic concept - customizing program (made4you)

RELIABILITY

Excellent quality and functional stability

- Proprietary development and production in Europe



LIFECYCLE

Hardware continuity for long lasting project needs

- Managed lifecycle up to 12 months

MEETS ENERGY STAR® 5.0 AND BLUE ANGEL REQUIREMENTS

Low power consumption and low costs, without any loss in performance.

- Effective power supply of maximum 87%



COMPONENTS

PROCESSOR

Intel® Core™2 Quad processor Q9650 (4 Cores / 4 Threads, 3.0 GHz, 12 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9550 (4 Cores / 4 Threads, 2.83 GHz, 12 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9505 (4 Cores / 4 Threads, 2.83 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Quad processor Q8300 (4 Cores / 4 Threads, 2.5 GHz, 4 MB, 1333 MHz)
Intel® Core™2 Duo processor E8600 (2 Cores / 2 Threads, 3.33 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E8500 (2 Cores / 2 Threads, 3.16 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E8400 (2 Cores / 2 Threads, 3.0 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E7600 (2 Cores / 2 Threads, 3.06 GHz, 3 MB, 1066 MHz)
Intel® Core™2 Duo processor E7500 (2 Cores / 2 Threads, 2.93 GHz, 3 MB, 1066 MHz)
Intel® Pentium® processor E6600 (2 Cores / 2 Threads, 3.06 GHz, 2 MB, 1066 MHz)
Intel® Pentium® processor E5700 (2 Cores / 2 Threads, 3.0 GHz, 2 MB, 800 MHz)
Intel® Pentium® processor E5500 (2 Cores / 2 Threads, 2.8 GHz, 2 MB, 800 MHz)
Intel® Pentium® processor E5400 (2 Cores / 2 Threads, 2.7 GHz, 2 MB, 800 MHz)
Intel® Celeron® processor E3400 (2C/2T, 2.6 GHz, 1 MB, 800 MHz)
Intel® Celeron® processor E3200 (2 Cores / 2 Threads, 2.4 GHz, 1 MB, 800 MHz)

OPERATING SYSTEM

Operating system optional preinstalled	Genuine Windows® 7 Starter (EM) 32-bit Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Microsoft® Windows® XP Professional (DVD)
Operating system compatible	openSUSE Linux Genuine Windows Vista®
Operating system notes	Dependent on configuration Windows 7® versions are: Microsoft Office 2007 ready Microsoft Office 2010 preloaded. Purchase a Product Key to activate a full Microsoft Office 2010 suite. Limited Windows XP support. Microsoft discontinued Windows XP certification on system level.

MEMORY MODULES

1 GB (1 module(s) 1 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM

HARD DISK DRIVES (INTERNAL)

SSD SATA, 128 GB, 2.5-inch
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.

Hard disk notes

Supporting NCQ and 3 GBit

GRAPHICS ADD ON CARDS (OPTIONAL)

DP to DVI-D (single link) Adapter Cable
DVI-D + DisplayPort Extension Adapter
DVI Extension Adapter
NVIDIA® GeForce® 9300GE display port low profile, 512 MB
NVIDIA® Quadro® NVS 290 low profile, 256 MB

DRIVES (OPTIONAL)

1.44 MB Floppy
Blu-ray Disc™ Triple Writer
DVD-ROM
DVD Super Multi
MultiCard Reader 20in1, 3.5-Inch

INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)

Parallel Interface

Base unit	ESPRIMO E3521 E-Star5
MAINBOARD	
Mainboard type	D3041
Formfactor	µATX
Chipset	Intel® G41
Processor socket	LGA 775
Processor quantity maximum	1
System bus (FSB / HT / QPI)	up to 1333 MHz
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	8 GB
Memory frequency	1066 MHz
Memory notes	Dual channel support. For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1000 MBit/s Realtek RTL8111DL
BIOS version	Phoenix 6.0
BIOS features	BIOS Flash EPROM update by software Recovery BIOS
Audio codec	Realtek ALC663
Audio features	High Definition audio, 5.1 surround sound
I/O CONTROLLER ON BOARD	
Serial ATA total	4
thereof eSATA	0
Controller functions	Serial ATA II 3 GBit
INTERFACES	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	8
USB front	2
USB rear	4
USB internal	2
VGA	1
DisplayPort	1 (optional)
DVI	1 (optional)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
Interface Module notes	Anytime USB charge functionality
INPUT DEVICE / COMPONENTS	
	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse
DRIVE BAYS	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"

SLOTS

PCI-Express x16	1 x (210 mm) low profile
PCI-Express x1	1 x (210 mm) low profile
PCI (32-bit / 33 MHz)	2 x (170/ 190 mm) low profile

GRAPHICS ON BOARD

Graphics brand name	Intel® GMA 4500
Shared video memory	up to 1759 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
Graphics features	DirectX 10 HDCP support OpenGL® 2.0
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

ELECTRICAL VALUES

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 86% / 88% / 85%) 0-Watt mode with hard-off switch
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	90 - 264 V
Operating line frequency range	47 - 63 Hz
Max. output of single power supply	250 W
Power factor correction/active power	active
Monitor outlet	No

POWER CONSUMPTION

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=b0ce6669-1ef6-4d5b-8e4d-d7064dbd3f26

HEAT DISSIPATION

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

Noise emission	According to ISO9296
----------------	----------------------

NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

Related Processors for noise	Intel® Core™2 Duo E8600
Noise Operation mode 1: ODD load (Blue angel requirement)	4.4 B / 29 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	4.1 B / 26 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	4.0 B / 25 dB(A)
Noise Operation mode 4: High load	4.1 B / 26 dB(A)
Noise Operation mode 5: Office applications	4.1 B / 26 dB(A)
Idle mode (Blue Angel requirement)	4.0 B / 24 dB(A)
Noise notes / description	A weighted sound power level L _{wad} (in B) / workplace related A-weighted sound pressure level L _{pAm} (in dB(A)), Bystander position

DIMENSIONS / WEIGHT / ENVIRONMENTAL

Dimensions (W x D x H)	330 x 405 x 104 mm
Operating position	Vertical / horizontal (optional, feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C

COMPLIANCE

Product	ESPRIMO E3521
Model	DTL1-3041
Germany	Blauer Engel / Blue Angel GS
Europe	CE
USA/Canada	FCC Class B CSA
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 EPEAT® Silver
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

ADDITIONAL SOFTWARE

Additional software (preinstalled)	Nero Essentials S (burning software)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink Power2Go BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics) Nero 9 Essentials XL

COMPATIBILITY (REFERENCES)

	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
--	--

MANAGEABILITY

Manageability features	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode)
DeskView features	WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu

SECURITY

Physical security	Kensington Lock support Eye for padlock
--------------------------	--

SECURITY

System security	Boot sector virus protection
	Write protect option for the Flash EPROM
	Boot protection for floppy disk / CD drive and write protection for floppy disk drive
	Control of all USB interfaces
User security	User and supervisor BIOS password
	Optional: Access protection via external SmartCard reader
	Optional: Access protection via internal SmartCard reader

PACKAGING INFORMATION

Packaging dimension	500x290x540 mm
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (g) EPS / PS	200g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

WARRANTY

Standard Warranty	1 year
Service level	Bring-In / On-Site Service (depending on country)

MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO E3521 E-Star 5.0, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu ESPRIMO E3521 E-Star 5.0, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/ESPRIMO>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>

**COPYRIGHTS**

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2010-09-30 CE-EN